

# Ovoid Sub 4.1

15" Bass reflex subwoofer



Ovoidal 4.1 is a long excursion bass reflex subwoofer in ovoidal axisymmetric closed structure, characterized by extreme sensitivity, dynamics and emission power, made with an incredibly rigid and light structure in durable composite materials.

Unlike all other alternatives currently available, this low-frequency speaker was made without technical and dimensional compromises, with structural technologies not present in the professional audio market. Thus it achieves maximum acoustic performance with an elegant design and a unique personality.

All other bass reflex subwoofers on the professional audio market are built inside wooden box structures. This technology is flawed due to structural resonances and internal acoustic problems related to stationary waves. Furthermore, the wooden structure is very heavy and is characterized by problems related to protection and durability, with little resistance to atmospheric agents.

Ovoidal 4.1 represents an exclusive technological innovation, built from high quality composite materials in a special ovoidal shell shape. The scratch-resistant glossy surfaces and the resistance to atmospheric agents, combined with a great power with an extremely high efficiency and a very high sensitivity, allow Ovoidal 4.1 to truly distinguish itself when compared to any product from the main competing brands, with direct radiation electroacoustic bass reflex technology. Ovoidal 4.1 guarantees the perfect loading of low frequencies in sensitivity, depth, control and SPL expressed by the usage of few watts. Ovoidal 4.1 use a single hi-quality transducer of 15"(380mm). The structure is rigid and very light (considering the overall weight and the dB/Kg ratio). The aesthetic impact is extraordinary and absolutely unique on the professional sound market.

## Features

- Strong impact from the visual point of view
- Special ultralight anti-resonance shell structure
- Very powerful sound emission
- Extreme sensitivity
- Excellent sound quality at all power levels
- Perfect adaptability to any musical genre
- Heavy duty composite construction, resistant to scratches and bumps
- Completely weather resistant
- Engineered for easy maintenance and repair
- Technologically advanced design
- Very light weight for easy transport
- Simple installation and interface
- Customization of color and surface
- Unique exclusive design

## Applications

Small club spaces  
Small outdoor events  
Small-scale live events requiring high sound quality

Max Size of audience within the range of dispersion for 4x Ovoidal 4.1 subs:

Indoor 300

Outdoor 200

(recommendations vary depending on the genre and the desired pressure)



## Architectural Specifications

The Ovoidal 4.1 is a long excursion bass reflex subwoofer in an ovoidal axisymmetric closed structure.

Built from high quality composite materials, highly resistant to damage from scratches and bumps. Absolute resistance to rain and sun. All metal parts are built from stainless steel.

Ovoidal 4.1 sensitivity is 97dB 1W/1m; the woofer is 15"(380mm). neodymium inside slug, 8Ohm or 4ohm (depending on the versions) ; 1000w nominal power handling , 2000w power on continuous program is the recommended amplifier power to exploit, fully, the transducer without any clipping in the amplifier. The Full Fat audio FFA 10000 is the recommended amplifier for this solution.

Size of the audience for 4 Ovoidal 4.1 would be indoor 300pp, outdoor 200pp. This varies depending on musical preferences.

### Warning:

This is a professional audio system with very high efficiency and sensitivity with acoustic emissions that could potentially cause hearing damage. Installation and use intended for experienced and qualified personnel. Safety DSP devices with a limiter function are recommended.

<b>TYPE</b>	Bass reflex subwoofer in ovoidal structure
<b>FREQUENCY RESPONSE</b>	35 Hz - 1,5 KHz
<b>TOTAL SENSITIVITY</b>	97 dB 1W/m
<b>NOMINAL IMPEDANCE</b>	8 Ohm or 4 Ohm (depending on the version)
<b>POWER HANDLING</b>	1000 W nominal, 2000 W continuous program
<b>MANAGE</b>	Amp 2000 W 8 Ohm or 4 Ohm depending on te version
<b>RECOMMENDED AMPLIFIER</b>	Full Fatt Audio FFA 10000
<b>DISPERSION</b>	Omnidirectional
<b>CONSTRUCTION MATERIALS</b>	Fiber-reinforced composite, stainless steel
<b>FINISH</b>	all ral color and texture on order
<b>PROTECTIVE GRILLES</b>	stainless steel on request
<b>CONNECTORS</b>	1x Neutrik NL4 or custom preference
<b>DIMENSIONS (with support)</b>	(W) 700 mm (H) 700 mm (D) 700 mm (W) 28 inch (H) 28 inch (D) 28 inch
<b>WEIGHT</b>	20 Kg (44 lb) w/o support



**Pequod Acoustics** Phone: +39 055 66 43 46

via del Madonnone, 25 Florence. Italy Mail: [info@pequodacoustics.com](mailto:info@pequodacoustics.com) Web: [www.pequodacoustics.com](http://www.pequodacoustics.com)